

電動スライダ セレクション

シリーズ名 タイプ名	型番 幅×高さ	電源電圧	リード [mm]	ストローク [mm]														最高速度 [mm/s]			上段：動的許容モーメント [N·m] 下段：静的許容モーメント [N·m]			水平可搬質量 [kg]								垂直可搬質量 [kg]			繰返し 位置決め精度 [mm]	定価 [円]	掲載 ページ		
																		200	400	600	800	2000	Mp	My	Mr	10	20	30	40	50	60	70	80	10				20	30
EZSシリーズ αSTEP AZ搭載 ストレートタイプ 折返しタイプ クリーンルーム対応	EZSM3 54×50mm	AC電源入力	12	50~700														800			4.2	4.2	10.5	7.5									3.5	±0.02	61,300~	30			
			6	50~700														400			26.4	26.4	52.0	15									7			31			
		DC電源入力	12	50~700														600			4.2	4.2	10.5	7.5									3.5			±0.02	64,600~	32~33	
			6	50~700														300			26.4	26.4	52.0	15									7					34~35	
		EZSM4 74×50mm	AC電源入力	12	50~700														800			8	8	27.8	15											7	±0.02	64,600~	32~33
				6	50~700														400			51.2	42.5	176	30											14(12.5)*			34~35
	DC電源入力		12	50~700														600			8	8	27.8	15									7	±0.02	87,000~	36			
			6	50~700														300			51.2	42.5	176	30									14(12.5)*			37			
	EZSM6 74×66.5mm	AC電源入力	12	50~850														800			45.7	37.5	55.6	30									15	±0.02	87,000~	36			
			6	50~850														400			290	187	340	60									30			37			
		DC電源入力	12	50~850														600			45.7	37.5	55.6	30									15			±0.02	57,500~	62	
			6	50~850														300			290	187	340	60									30					63~64	
EASシリーズ αSTEP AZ搭載		EASM2 40×38mm	DC電源入力	6	50~300														300			2.4	1.5	4.6	7.5											2.5	±0.02	64,600~	63~64
				3	50~300														150			4.0	4.0	7.7	15											5			65~66
	AC電源入力	12	50~500														800			16.3	4.8	15.0	15									7	±0.02	137,500~	88				
		6	50~500														400			58.3	16.0	53.3	30									14			88				
EASM4 58.4×60mm	DC電源入力	12	50~500														600			16.3	4.8	15.0	15									7	±0.02	137,500~	88				
		6	50~500														300			58.3	16.0	53.3	30									14			88				
EZSHシリーズ αSTEP AZ搭載	EZSHM6 66.4×64mm	AC電源入力	30	200~1300														1800			27.3	21.8	45.8	15									7.5	±0.005	137,500~	88			
			20	200~1300														1200			335	276	440	25									12.5			88			

* ()内は、折返しタイプの値です。